

# DIGITAL AUTO GAS FILLER OF THE WORLD

## DIGITAL AUTO GAS FILLER CONNECT VALVE



1. Explosion proof digital auto butane filler ..... 3
2. Special explosion proof digital auto butane filler ..... 4
3. Explosion proof digital auto propane filler ..... 5
4. Butane Connect valve ..... 6
5. Propane Connect valve ..... 6
6. Handling Items ..... 7



KOREA METER INTERNATIONAL

인천광역시 서구 경서동 696-3, 13B-1L  
 TEL : (032) 561-1292-3  
 FAX : (032) 561-1295  
 E-mail : koreameter@yahoo.co.kr

KMI KOREA METER INTERNATIONAL

## Explosion proof digital auto butane filler

### FEATURES

- Indicator has been specially developed for LP gas filling to cylinder.
- Can manage stock, amount, accumulate data.
- Fuction of watch-dog(Fuction of system restoring).
- Fuction of photo-coupler.
- Digital parts indicate the correct quantity of filled gas.
- Weight back-up(Even though the electricity is fail previous weight remains.
- It will set up ninety nine kinds of guns to shortening height setting screens.
- It control the gas flow and we assemble the machine easy to repair.

### POS SYSTEM(Optional)

- Print port,computer interface RS422.
- 1:1 Interface and 1:24 Interface.
- USB, PC program

### General Specification

ITEMS	SPECIFICATIONS
WEIGHT RANGE	0~150kg
GRADUATION UNIT	20~50g
A/D RESOLVING POWER	520,000 Count(19bit)
MAIN DISPLAY TYPE	7-Segment 6-digit red FND
SUB DISPLAY TYPE	7-Segment 14-digit red FND
MEASUREMENT TYPE	LOAD CELL
REGULAR VOLTAGE	SMPS Free Voltage (85V~265V)
POWER CONSUMPTION	30W
AVAILABLE TEMPERATURE	-25℃~50℃
PNEUMATIC AIR PRESSURE	4~5kg/cm <sup>2</sup>
MEASUREMENT(m <sup>3</sup> /m)	420(W)×710(D)×1880(H)
TOTAL WEIGHT	115kg



## Special explosion proof digital auto butane filler

### FEATURES

- Indicator has been specially developed for LP gas filling to cylinder.
- Can manage stock, amount, accumulate data.
- Fuction of watch-dog(Fuction of system restoring).
- Fuction of photo-coupler.
- Digital parts indicate the correct quantity of filled gas.
- Weight back-up(Even though the electricity is fail previous weight remains.
- It will set up ninety nine kinds of guns to shortening height setting screens.
- It control the gas flow and we assemble the machine easy to repair.

### POS SYSTEM(Optional)

- Print port,computer interface RS422.
- 1:1 Interface and 1:24 Interface.
- USB, PC program

### General Specification

ITEMS	SPECIFICATIONS
WEIGHT RANGE	0~100kg
GRADUATION UNIT	20~50g
A/D RESOLVING POWER	520,000 Count(19bit)
MAIN DISPLAY TYPE	7-Segment 6-digit red FND
SUB DISPLAY TYPE	7-Segment 14-digit red FND
MEASUREMENT TYPE	LOAD CELL
REGULAR VOLTAGE	SMPS Free Voltage (85V~265V)
POWER CONSUMPTION	30W
AVAILABLE TEMPERATURE	-25℃~50℃
PNEUMATIC AIR PRESSURE	4~5kg/cm <sup>2</sup>
MEASUREMENT(m <sup>3</sup> /m)	420(W)×710(D)×1290(H)
TOTAL WEIGHT	95kg



## Explosion proof digital auto propane filler

### FEATURES

- Indicator has been specially developed for LP gas filling to cylinder.
- Can manage stock, amount, accumulate data.
- Fuction of watch-dog(Fuction of system restoring).
- Fuction of photo-coupler.
- Digital parts indicate the correct quantity of filled gas.
- Weight back-up(Even though the electricity is fail previous weight remains.
- It will set up ninety nine kinds of guns to shortening height setting screens.
- It control the gas flow and we assemble the machine easy to repair.

### POS SYSTEM(Optional)

- Print port,computer interface RS422.
- 1:1 Interface and 1:24 Interface.
- USB,PC program

### General Specification

ITEMS	SPECIFICATIONS
WEIGHT RANGE	0~150kg
GRADUATION UNIT	20~50g
A/D RESOLVING POWER	520,000 Count(19bit)
MAIN DISPLAY TYPE	7-Segment 6-digit red FND
SUB DISPLAY TYPE	7-Segment 14-digit red FND
MEASUREMENT TYPE	LOAD CELL
REGULAR VOLTAGE	SMPS Free Voltage (85V~265V)
POWER CONSUMPTION	30W
AVAILABLE TEMPERATURE	-25℃~50℃
PNEUMATIC AIR PRESSURE	4~5kg/cm <sup>2</sup>
MEASUREMENT(m <sup>3</sup> /m)	420(W)×710(D)×1880(H)
TOTAL WEIGHT	115kg



## Butane connect valve

### FEATURES

- Connect valve has been specially developed for LP gas filling to cylinder.
- This is connecting to cylinder for gas filling and can be open the entrance automatically after connection.
- This is made easy to change the consumption goods.It is attached K-100 IB,K-200 IB.



### General Specification

ITEMS	SPECIFICATIONS
WORKING AIR PRESSURE	4~5kg/cm <sup>2</sup>
CONNECTION SIZE	Gas line : PT 1/2", Air line : ϕ8
DIMENSION	ϕ65×240mm
TOTAL WEIGHT	2kg

## Propane connect valve

### FEATURES

- Connect valve has been specially developed for LP gas filling to cylinder.
- This is connecting to cylinder for gas filling and can be open the entrance automatically after connection.
- This is made easy to change the consumption goods.It is attached K-100 IB,K-200 IB.



### General Specification

ITEMS	SPECIFICATIONS
WORKING AIR PRESSURE	4~5kg/cm <sup>2</sup>
CONNECTION SIZE	Gas line : PT 1/2", Air line : ϕ8
DIMENSION	ϕ64×480mm
TOTAL WEIGHT	1.8kg

## LPG COMPRESSOR

